

7400 A

Anaesthesia Machine



- Classical and widely used anaesthesia machine, single vaporizer
- 4-tubes flowmeter
- Suitable for adult and pediatric
- High quality and durable design
- CE marked, meets clinical safety requirement of EU
- Solid coating and anti-dust smooth surface

Technical Specification

Physical & Environmental Specification

- Dimensions(W×H×D): 890 × 1335 × 620mm
- Weight: 110kg
- Storage temperature: -20~+55°C
- Working temperature: +10~+40°C
- Storage humidity: ≤93%

Electrical Specification

- Mains: 110-240V AC, 50-60Hz
- Power consumption: ≤50W

Pneumatic Specification

- Gas supply: O₂, N₂O: 0.28-0.6Mpa
- Flowmeters: O₂: 0-1L/min; 1-10L/min
N₂O: 0-1L/min; 1-10L/min
- Gas system: O₂ deficiency alarm
Hypoxic guard system
O₂ flush: 35-75L/min
- Working mode: Closed, Semi-closed, Semi-open
- Driven mode: Pneumatically driven and electronically controlled
- Operating mode: Man. / Vent.
- Safety valve: ≤8kpa

Ventilator Specification

- Patient type: Adult, pediatric
- Ventilation modes: IPPV, Manual
- Setting: Touch key
- Tidal volume: 0-1500ml
- Ventilation frequency: 6-60bpm
- I:E ratio: 2:1-1:4
- P_{PEEP}: 0-20 cmH₂O
- High pressure: 21-60cmH₂O
- Low pressure: 0-20cmH₂O
- Monitoring: Display: High quality LED
Pressure: P_{aw}
Volumes: V_t
Breath rate
- Alarm: Pressure: P_{aw} high/low limit
Low O₂ supply pressure
Power failure
Alarm silence: ≤120s

Vaporizer

- Support 1 vaporizer (Selectatec compatible)
- Agent type: Halothane, Enflurane, Isoflurane , Sevoflurane available.